



# **D5304-1 CROSSBOLT SPACER**

## **NOTES:**

- 1) MATERIAL: 6061-T4/-T42 SEAMLESS ALUMINUM TUBING PER WW-T-700/6, AMS 4081, OR ASTM B210/B221/B241  
REF DART SPEC M6061T4T0.750W.125  
OR  
6061-T6/-T62/-T6510/-T6511 SEAMLESS TUBING PER WW-T-700/6 OR  
QQ-A-200/8 OR QQ-A-225/8 OR AMS 4080 OR AMS 4082 OR AMS 4083  
OR ASTM B210 OR ASTM B241. REF DART SPEC M6061T6T0.750W.125  
HEAT TREAT TO T4/-T42 CONDITION. MIN UTS = 30 KSI (60 HREW MIN)
- 2) FINISH: CHEMICAL CONVERSION COAT PER DART QSI 005 4.1
- 3) TOLERANCES: PER DART QSI 018 UNLESS OTHERWISE NOTED
- 4) UNITS: INCHES UNLESS OTHERWISE NOTED
- 5) BREAK SHARP EDGES: 0.005 TO 0.010 MAX
- 6) IDENTIFICATION: NONE
- 7) WEIGHT: 0.05 lbs

**RELEASED**  
2016-02-04  
ECN 16-514

APPROVED

A	NEW ISSUE	AP	15.11.02
REV.	DESCRIPTION	BY	DATE
DESIGN	AP	<b>DART AEROSPACE USA, INC.</b> EUGENE, OR	
DRAWN	AP		
CHECKED	AJS	DRAWING NO.	REV. A
MFG. APPR.	JLM	D5304	SHEET 1 OF 1
APPROVED	WM	TITLE	SCALE
DE APPR.	DS	CROSSBOLT SPACER	NTS
DATE	15.11.02	<small>COPYRIGHT © 2015 BY DART AEROSPACE USA, INC. THIS DOCUMENT IS PRIVATE AND CONFIDENTIAL AND IS SUPPLIED ON THE EXPRESS CONDITION THAT IT IS NOT TO BE USED FOR ANY PURPOSE OR COPIED OR COMMUNICATED TO ANY OTHER PERSON WITHOUT WRITTEN PERMISSION FROM DART AEROSPACE USA, INC.</small>	